

Intellian

C700

IRIDIUM CERTUS®
Winterized Maritime Terminal



FEATURES

THE MOST POWERFUL IRIDIUM CERTUS TERMINAL AVAILABLE

The Intellian C700 uses the most powerful 12 patch phased-array antenna to deliver the highest performing and most reliable Certus® terminal, especially at low angles of elevation, which is critical in a maritime environment. The C700 provides the highest IP data speeds of up to 704 Kbps, and the H2 class high power amplifier supports uplink data speeds up to 352 Kbps as standard. Customers will gain both scalability and advanced performance over the Certus network whenever needed.

The winterized C700 terminal is designed to withstand extreme low temperature environments, while maintaining its high end performance. It allows the terminal to operate in harsh weather conditions like the polar regions.

BEST-IN-CLASS FEATURES AND VALUE

The C700 delivers unparalleled features and value to users at both a technology and operational level. The C700 offers a variety of features such as three high-quality voice lines, a built-in firewall, 3G/LET WAN port, and soft PABX. These technical capabilities and GMDSS readiness make it ideal for both vessel operations and crew welfare services.

It's easy to install and simple configuration, combined with Intellian's ability to ship from global logistic centers provides a lower cost of shipment and installation for customers and increased flexibility. The industry leading 3 year warranty policy and global service partners provide customers with reassurance and dependable communications wherever they operate.

A PERFECT VSAT COMPANION SOLUTION

Intellian is the No. 1 maritime VSAT manufacturer and global market leader. All Intellian C700 terminals are optimized as VSAT companion devices and can be delivered as a turnkey solution with a rack mount version available. The combination of Intellian's innovative VSAT Ku-band products, including the NX Series and the C700 system provide access to the most advanced and reliable connectivity products available.

The C700 capabilities provide a more seamless connection and user experience when switching from VSAT. The Aptus platform provides advanced management and control for remote support and diagnostics, including easy to use API's, making it ideal as a VSAT out-of-band management solution.

SYSTEM HIGHLIGHTS

- Designed for extreme low temperature conditions, like the polar regions. (ADU operating temp. -50°C ~ +55°C)
- H2 antenna amplifier for 352 Kbps uplink service
- Excellent low elevation angle performance handling heavy ship motion
- Easy installation and simple configuration
- Single coaxial cable antenna connection
- Built-in firewall and user threat management
- GMDSS ready
- Three simultaneous high quality voice lines
- 4-Port Ethernet (LAN) PoE and WAN
- Connection up to 16 SIP phones with Soft PBX function
- Designed for minimum 10-year operational lifetime
- 3 year global warranty - parts and labor
- Designed for extremely harsh cold weather regions

C700

IRIDIUM SERVICES

Voice	3 simultaneous HD voice lines
IP Data (Background)	Uplink: up to 352 Kbps / Downlink: up to 704 Kbps
IP Streaming	Uplink/Downlink: up to 256 Kbps
Short Burst Data	Yes

PHYSICAL

ADU Dimensions	700 x 720 mm / 27.5" x 28.3"
ADU Weight	21kg (46.3 lbs)
BDU Dimensions	280 x 190 x 41 mm / 11" x 7.2" x 1.45"
BDU Weight	1.2 kg (stand-alone type) / 2.6 lb

ANTENNA POWER

DC Input	10.8 ~ 30 V DC
Power (max)	120 W

HEATING DEVICE POWER

AC Input	220VAC, 0.91A
Power (max)	200 W

RF / ANTENNA

Tx Frequency	1616 MHz ~ 1626.0 MHz
Rx Frequency	1616 MHz ~ 1626.5 MHz
Antenna Gain	HGA 2 Class
Antenna Connectors	TNC female (ADU) – TNC female (BDU)
GNSS	GPS, GLONAS, Galileo
Wi-Fi	802.11 b/g

APPROVAL

Certification	CE/RED, FCC, RMRS
---------------	-------------------

ENVIRONMENTAL CONDITIONS


Operating Temp. range	ADU: -50°C ~ + 55°C, BDU: -15°C ~ + 55°C
Operating Humidity range	More than 95%
Water Ingress	ADU: IP56, BDU: IP31
Shock & Vibration	Shock: IEC60068-2-27 (operation), IEC60721-3-6 Class 6M3 (survival) Vibration: IEC60945 (operation), IEC60721-3-6 Class 6M3 (survival)

I/O


LAN	3 x RJ45 (2 PoE)
WAN	1 x RJ45
Analog Phone	1 x RJ14 (2 x Analog Phone)
Wireless	1 Wi-Fi (SMA RP)
I/O	10 pin GPIO
Etc.	SIM, Reset, On/Off, Ground

SYSTEM DIMENSION


ADU




BDU



19" Rack-Mount Bracket Assembled



SYSTEM DIAGRAM



Esatcom Inc.
www.esatcom.com

Tel:
718.276.0800

Email:
sales@esatcom.com

