



# LNAKU20NP

## Single-Band Ku-Band LNA

**Band:** 11.7 - 12.75 GHz

**Output Connector:** N - 50 Ohm

**Power Connector:** MS3112E10-6P



### KEY SPECIFICATIONS

<b>Band</b>	Ku-Band
<b>Input Frequency Band 1</b>	11.70 - 12.75 GHz
<b>Noise Figure</b>	0.8 dB
<b>Required Current</b>	250 mA

### RF SPECIFICATIONS

<b>Conversion Gain</b>	50 dB min., 55 dB typ., 60 dB max.
<b>Gain Flatness</b>	4 dB p-p
<b>Gain Ripple (At Per 36 M Hz)</b>	1 dB p-p
<b>Input V S W R</b>	2.0 : 1
<b>Output P1D B</b>	+ 5 dBm
<b>Output V S W R</b>	2.0 : 1

### ELECTRICAL SPECIFICATIONS

<b>Power Connector</b>	MS3112E10-6P
<b>Power Supply</b>	12-24 VDC

### INTERFACE SPECIFICATIONS

<b>Input W/ G Flange</b>	WR 75
--------------------------	-------

### ENVIRONMENTAL SPECIFICATIONS





Temperature Operational	-40 to +60°C
Waterproofing	IP 67
Weight	450 g

## PHYSICAL SPECIFICATIONS

Dimensions ( Lx Wx H )	60.0 x 41.6 x 111.5 mm
------------------------	------------------------

## LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	ECCN Number	Shipping Package
8517690000	Made in Korea	EAR99	145 x 95 x 65 mm   475 g

## MECHANICAL DIAGRAMS

