



LNAKU10NC

Single-Band Ku-Band LNA

Band: 10.7 - 11.7 GHz

Output Connector: N - 50 Ohm

Power Connector: Output connector



KEY SPECIFICATIONS

| | |
|-------------------------------|-------------------|
| Band | Ku-Band |
| Input Frequency Band 1 | 10.70 - 11.70 GHz |
| Noise Figure | 0.8 dB |
| Required Current | 250 mA |

RF SPECIFICATIONS

| | |
|-------------------------------------|------------------------------------|
| Conversion Gain | 50 dB min., 55 dB typ., 60 dB max. |
| Gain Flatness | 4 dB p-p |
| Gain Ripple (At Per 36 M Hz) | 1 dB p-p |
| Input V S W R | 2.0 : 1 |
| Output P1D B | + 5 dBm |
| Output V S W R | 2.0 : 1 |

ELECTRICAL SPECIFICATIONS

| | |
|------------------------|------------------|
| Power Connector | Output connector |
| Power Supply | 12-24 VDC |

INTERFACE SPECIFICATIONS

| | |
|--------------------------|-------|
| Input W/ G Flange | WR 75 |
|--------------------------|-------|

ENVIRONMENTAL SPECIFICATIONS





| | |
|-------------------------|--------------|
| Temperature Operational | -40 to +60°C |
| Waterproofing | IP 67 |
| Weight | 450 g |

PHYSICAL SPECIFICATIONS

| | |
|------------------------|------------------------|
| Dimensions (Lx Wx H) | 60.0 x 41.6 x 111.5 mm |
|------------------------|------------------------|

LOGISTICS SPECIFICATIONS

| HS Code | Country of Origin | ECCN Number | Shipping Package |
|------------|-------------------|-------------|--------------------------|
| 8517690000 | Made in Korea | EAR99 | 145 x 95 x 65 mm 475 g |

MECHANICAL DIAGRAMS

