

Innovative Communication Solutions

9700HICDN

9700 Dual-Band Ka-Band PLL LNB

Frequency: 20.2 - 21.2 & 21.2 - 22.2 GHz

W/G Isolator: Yes Connector: N: 50 Ohm



KEY SPECIFICATIONS

Band Ka-Band Input Frequency Band 1 20.20 - 21.20 GHz Input Frequency Band 2 21.20 - 22.20 GHz LO Frequency 1 19.25 GHz LO Frequency 2 20.25 GHz LO Stability ±70 kHz LO Type PLL 1.5 dB Noise Figure Max Noise Figure Typ 1.8 dB Of Onboard Los Dual-band Output Frequency Band 1 950 - 1950 MHz **Output Frequency Band 2** 950 - 1950 MHz

RF SPECIFICATIONS

Control Signal 1 13V / No Tone Control Signal 2 18V / No Tone Conversion Gain Max 65 dB Conversion Gain Min 55 dB 60 dB Conversion Gain Typ Gain Flatness (over Full Band) ≤ 5 dB p-p Input VSWR 2.5:1 max. Output P1db + 5 dBm min.





Innovative Communication Solutions

Output VSWR2.5 : 1 max.Phase Noise 100khz Offset Max-95 dBc/HzPhase Noise 10khz Offset Max-78 dBc/HzPhase Noise 1khz Offset Max-70 dBc/Hz

ELECTRICAL SPECIFICATIONS

Power Requirements +12 to +24V DC

INTERFACE SPECIFICATIONS

RF Input Connector WR-42 waveguide grooved

ENVIRONMENTAL SPECIFICATIONS

Temperature Operational -40 to +60°C
Temperature Storage -40 to +80°C

PHYSICAL SPECIFICATIONS

Product Dimensions (LxWxH) 120 x 60 x 45 mm


Product Weight 420 g (14.82 oz)

LOGISTICS SPECIFICATIONS

HS Code Country of Origin Ex Works ECCN Number Unit Package

8517690000 Made in Korea Korea EAR99 N/A | N/A

HOW TO ORDER




MECHANICAL DIAGRAMS





Innovative Communication Solutions







Tel 718.799.0084 Email sales@esatcom.com