



ELMTBKU050H-SF-M

ELEMENT 50W Ku-Band MINIBUC

Input Frequency: 14.00 - 14.50 GHz

Input Connector: F-Connector

M&C Function: RS-232 & RS-485



KEY SPECIFICATIONS

Band	Ku-Band
External Ref Freq	10 MHz, -5 to +5 dBm
Input Frequency Band 1	950 - 1450 MHz
LO Frequency 1	13.05 GHz
Output Frequency Band 1	14.00 - 14.50 GHz
Output Power Rated	50W
Reference Type	Internal Reference

RF SPECIFICATIONS

Gain Flatness (over 54mhz)	1.5 dB
Gain Flatness (over Full Band)	4 dB
Gain Flatness (over Temperature)	4 dB
Input VSWR	2 : 1 max.
Linear Gain	72 dB typ.
Output P1db	+47 dBm typ. / +46 dBm min. over temperature
Output Spurious In Band	-60 dBc
Output Spurious Out Of Band	-50 dBc
Output VSWR	2 : 1 max.
Phase Noise 100khz Offset Max	-95 dBc/Hz
Phase Noise 10khz Offset Max	-85 dBc/Hz
Phase Noise 1khz Offset Max	-75 dBc/Hz

ELECTRICAL SPECIFICATIONS

Current Consumption	390W max.
---------------------	-----------



Power Requirements

+36 to +60V DC

INTERFACE SPECIFICATIONS

Frequency Sense

Non-inverted

IF Connector

F-Connector

ENVIRONMENTAL SPECIFICATIONS

Humidity

Up to 100%

IP Rating

IP 55

Temperature Operational

-40 to +55°C

Temperature Storage

-40 to +60°C

PHYSICAL SPECIFICATIONS

Internal Function

Lock detector shuts off Tx in case of LO unlocked

Product Dimensions (LxWxH)

245 x 125 x 125 mm

Product Weight


4 kg

LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8543700000	Made in Korea	Korea	EAR99	290 x 270 x 250 mm 4.5 kg

HOW TO ORDER

ELMTB KU050HT-EF-E



MECHANICAL DIAGRAMS

