



ELMTBKU040-SN

ELEMENT 40W Ku-Band EXT REF MINIBUC

Input Frequency: 14.00 - 14.50 GHz

Input Connector: N-Connector

M&C Function: No M&C Function



KEY SPECIFICATIONS

Band	Ku-Band
External Ref Freq	10 MHz, -5 to +5 dBm
Input Frequency Band 1	950 - 1450 MHz
LO Frequency 1	13.05 GHz
Output Frequency Band 1	14.00 - 14.50 GHz
Output Power Rated	40W
Reference Type	External Reference

RF SPECIFICATIONS

Gain Flatness (over 54mhz)	1.5 dB
Gain Flatness (over Full Band)	4 dB
Gain Flatness (over Temperature)	4 dB
Input VSWR	2 : 1 max.
Linear Gain	72 dB typ.
Output P1db	+46 dBm min. over temperature
Output Spurious In Band	-60 dBc
Output Spurious Out Of Band	-50 dBc
Output VSWR	2 : 1 max.
Phase Noise 100khz Offset Max	-95 dBc/Hz
Phase Noise 10khz Offset Max	-140 dBc/Hz max.
Phase Noise 1khz Offset Max	-135 dBc/Hz max.

ELECTRICAL SPECIFICATIONS

Current Consumption	390W max.
---------------------	-----------





Power Requirements

+36 to +60V DC

INTERFACE SPECIFICATIONS

Frequency Sense

Non-inverted

IF Connector

N-Connector

ENVIRONMENTAL SPECIFICATIONS

Humidity

Up to 100%

IP Rating

IP 55

Temperature Operational

-40 to +55°C

PHYSICAL SPECIFICATIONS

Internal Function

Lock detector shuts off Tx in case of LO unlocked

Product Dimensions (LxWxH)

245 x 125 x 125 mm

Product Weight

4 kg

LOGISTICS SPECIFICATIONS

HS Code

Country of Origin

Ex Works

ECCN Number

Unit Package

8543700000

Made in Korea


Korea

EAR99

290 x 270 x 250 mm |
4.5 kg

HOW TO ORDER

ELMTBKU040HT-EF-E




MECHANICAL DIAGRAMS





Norsat
International Inc.

Innovative Communication Solutions



Esatcom Inc
Norsat authorized distributor
www.esatcom.com

Tel
718.276.0800

Email
sales@esatcom.com

