



ELMTBC050H-IF-DM

ELEMENT 50W C-Band BUC

Input Frequency: I: 6.725 - 7.025 GHz

Input Connector: F-Connector

Input Voltage + M&C: 36-60 VDC + RS-232 &

Function: RS-485



KEY SPECIFICATIONS

Band	C-Band
External Ref Freq	10 MHz, -5 to +5 dBm
Input Frequency Band 1	975 - 1275 MHz
LO Frequency 1	5.75 GHz
Output Frequency Band 1	6.725 - 7.025 GHz
Output Power Rated	50W
Reference Type	Internal Reference

RF SPECIFICATIONS

Gain Flatness (over 54mhz)	1.5 dB
Gain Flatness (over Full Band)	4 dB
Gain Flatness (over Temperature)	4 dB
Input VSWR	2 : 1 max.
Linear Gain	73 dB typ.
Output P1db	+47 dBm min. over temperature
Output Spurious In Band	-60 dBc
Output Spurious Out Of Band	-50 dBc
Output VSWR	2 : 1 max.
Phase Noise 100khz Offset Max	-95 dBc/Hz
Phase Noise 10khz Offset Max	-85 dBc/Hz
Phase Noise 1khz Offset Max	-75 dBc/Hz





ELECTRICAL SPECIFICATIONS

Current Consumption	290W DC max.
Power Requirements	+36 to +60V DC

INTERFACE SPECIFICATIONS

Frequency Sense	Non-inverted
IF Connector	F-Connector

ENVIRONMENTAL SPECIFICATIONS

Humidity	Up to 100%
IP Rating	IP 54
Temperature Operational	-40 to +55°C
Temperature Storage	-40 to +75°C

PHYSICAL SPECIFICATIONS

Internal Function	Lock detector shuts off Tx in case of LO unlocked
Product Dimensions (LxWxH)	220 x 195 x 138 mm
Product Weight	6.0 kg

LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8543700000	Made in Korea	Korea	EAR99	290 x 270 x 250 mm 8.5 kg

HOW TO ORDER

ELMTBC050HT-SF-AE

ELEMENT SERIES	C: C-Band	POWER 050: 50W	M&C FUNCTION	BLANK: Opt-out E: Ethernet M: RS-232 & RS-485
	B: BUC		INPUT VOLTAGE	A: AC Power Option D: DC Power Option
			CONNECTOR	F: 75 Ohm N: 50 Ohm
			FREQUENCY	S: 5.850 - 6.425 GHz (Standard) P: 6.425 - 6.725 GHz (Palapa) I: 6.725 - 7.025 GHz (Insat) W: 5.850 - 6.725 GHz (Wide)
			OPERATING TEMPERATURE	BLANK: -40 to 55°C T: -40 to 60°C
			REFERENCE	BLANK: External Reference H: Internal Reference

MECHANICAL DIAGRAMS





F-Female & N-Female Connector

LED Indicator

A : VDC
C : GND

A : VDD
C : GND

0.0000

A 1 RS232 Tx

B 1 RS232 Rx

C = GND

E	RS4
F	RS4

F : RS485 TRx+

H : Ethernet Rx+
I : Ethernet Rx-

K : Ethernet Tx+

L : Ethernet Tx-

MS3112E 14-5P

- MS3112E 14-19S

3-M6 depth 7


CPR-137G

8-No.10 32UNF, depth 7

— 2-M6 depth6

138

Unit : mm





Norsat
International Inc.

Innovative Communication Solutions



