

# XTREME 160-C

## 160 Port Fan-In L-Band RF Matrix Switch



XTREME 160-C

### General Description:

The **XTREME 160-C** next generation L-band matrix switch features up to 160 ports in a compact 4 RU chassis. The **XTREME 160-C** is a full fan-in (combining), non-blocking switch where one or multiple inputs can be routed to an output. The **XTREME 160-C** features an industry exclusive flexible matrix architecture (patented) that supports both symmetric and asymmetric configurations of 160 combined inputs and outputs in a single chassis. Asymmetric configurations such as 128x32 can be implemented as well as the standard 64x64 configuration. The **XTREME 160-C** is designed for maximum reliability with redundant power supplies and control cards.

### Features & Benefits:

- Compact modular design with a variety of configurations adding to 160 ports in 4 RU
- Easy hot-swap of all RF cards, power supplies and control cards
- Option for fiber optic inputs
- Independent input and output gain control
- Remotely controlled via web browser GUI interface, SNMP, Telnet or TCP/IP via customer supplied PC
- Redundant hot-swap control cards

Specifications: *1	XTREME 160-C
Configurations:	64x64, 80x48, 128x32
RF Connectors:	F-Type, BNC 75 Ω or 50 Ω, SMA, Mixed or Optical Input Receivers SC/APC or LC/APC
Impedance:	75 Ω or 50 Ω
Operating Frequency:	850-2450 MHz
Frequency Response:	+/-1.5 dB (950-2150 MHz), +/-2.0 dB (850-2450 MHz) +/-0.5 dB Over Any 36 MHz Channel
Input P1dB:	0 dBm
Noise Figure:	14 dB @ 0 dB Gain
OIP3:	+10 dBm
Input Return Loss:	14 dB
Output Return Loss:	14 dB
Isolation (input-to-input):	60 dB
Isolation (output-to-output):	60 dB
Isolation (input-to-output):	55 dB (950-2150 MHz), 50 dB (850-2450 MHz)
Input Gain Range:	-23.5 to +8 dB in .5 dB Steps
Output Gain Range:	-23.5 to +8 dB in .5 dB Steps
Local Control:	8.4" Touchscreen Display
Remote Control:	SNMP, TELNET, TCP/IP, Web Browser Interface Via Ethernet
Power Requirements:	100-240 VAC Autoranging, 50/60 Hz
Power Consumption:	160 W
Size:	4 RU: 7"H x 19"W x 23.25 D"

\*Specifications may vary with connector type. See individual specification sheet for specific performance data.

\*Specifications may vary with connector type and size configuration. See individual specification sheet for specific performance data.