

## TSC-5000 Transport Stream Converter ASI & 310M



## **TRANSPORT STREAM CONVERTER**

The **TSC-5000** is a robust transport stream format converter (TSC) and is compliant with both ATSC and DVB standards and is ATSC Mobile DTV Ready.

The **TSC-5000** converts transport streams between ASI, and SMPTE 310M formats. It accepts both formats and will output both formats simultaneously.

The **TSC-5000** is controlled via a web server user interface and allows the user to configure and monitor the unit status. Adhering to the concept of our TSC family of products, the **TSC-5000** is designed for easy operation.

The **TSC-5000** has GPI/O, dual power supplies for reliability and is field upgradable.

## **FEATURES LIST**

- ✓ All outputs active simultaneously
- ✓ ASTC Mobile DTV Ready
- ✓ Supports 188 & 204 byte packets
- ✓ Controlled via web server user interface
- ✓ Equalized and amplified Loop out (ASI and SMPTE 310M Only)
- ✓ Remote status indicator via web server user interface
- ✓ Manual front panel reset button
- ✓ Relay bypass in the event of power failure
- ✓ Rear panel GPI/O connector
- ✓ Field upgradable
- ✓ Dual power supplies for reliability
- ✓ Save/Load user defined/power up configurations
- ✓ User login management controls

VISION + INNOVATION



# TSC-5000 Transport Stream Converter

ASI & 310M



## **SPECIFICATIONS**

#### ASI

- Connector: BNC 75 ohm
- Data Rate to: 50 Mbps +/- 10ppm in, +/-3ppm out
- Logic Levels: 800mV +/-10%
- Data Rate: Accuracy: 3ppm

#### **SMPTE 310M**

- Connector: BNC 75 ohm
- Data Rate: 19.392658 Mbps
- Format: Bi-phase mark coding
- Max jitter: 1ppm

#### Network

- Single 100/1000 Base-TX Ethernet Port (RJ-45)
- User Interface I/O Setting



Made in the USA

	NNOVATIONS	
About		
<u>Status</u>		
<u>Admin</u>	Input Setting	
Configuration	Packet Size	188  20
I/O Setting		
Web Server	310 Output Setting	
Save/Load	Enable Phase Lock Loop	
Firmware	Enable Null Packet Insertion	
Log Out	Remove Null Packet from Input TS	
	Submit Refresh	

## Electrical

- Maximum Power: 25W
- Supply voltage range: 85-264 VAC/47-63HZ
- Power Plug: IEC-C-19
- Cooling Fan Capacity: 6CFM back exhaust

### Physical

- Height: 1.75 inches (44.45mm) 1RU
- Width: 19 inches (482.6mm)
- Depth: 14 inches (355.6mm)
- Weight: 3.5 Lbs (1.59kg)

March 2024. Specifications subject to change without notice.



Esatcom Inc DTV authorized distributor www.esatcom.com

## **VISION + INNOVATION**

Tel 718.799.0084