

Satcom & Antenna Technologies Division



Transmit Quality Precision SMC Reflector

Fine Elevation and Azimuth Adjustments

Wide Band Ku RxO Feed

Linear Single or Dual Polarity

Durable and Rugged Construction for Ease of Shipping and Handling

Heavy Gauge Pre-Galvanized Steel Az/EI Mount

Overview

CPI Satcom & Communications Technologies Inc (CPI SAT) 1.2m Ku-Band VSAT Antenna Series 1122 is ideally suited for demanding commercial applications. The one-piece compression molded reflector is precision manufactured for high-efficiency Ku-Band operation. The Az/EI mount is designed for easy installation on standard 2-7/8" OD or 3.0" OD Installation Mounts, and features fine Azimuth and Elevation Adjustments. The Az/EI mount is constructed from heavy gauge pre-galvanized steel for strength and corrosion resistance. The Series 1122 RxO Antenna utilizes the same reflector and Az/EI mount as the 1122 RxTx antenna, for future upgrades.

Electrical

- **Antenna Size**
 - 1.2 m (48 in.)
- **Operating Frequency (GHz)**
 - Receive = 10.70-12.75 GHz
- **Midband Gain (+/- .3dBi)**
 - Receive = 41.5 dBi
- **Antenna Noise Temperature**
 - 20° Elevation = 46° K
 - 30° Elevation = 43° K
- **Antenna Sidelobe Envelope**
 - Per ITU-R S.580-6
- **Antenna Beamwidth**
 - Receive = 1.5°
- **Polarization**
 - Linear, Orthogonal
- **Cross-Pol Isolation**
 - 30 dB on Axis

Feed Specifications – Dual Polarity Feed

- **Port-Port Isolation**
 - 30 dB Typical
- **VSWR**
 - 1.5:1 Max
- **Insertion Loss**
 - 0.3 dB Max

Mechanical Performance

- **Reflector Material**
 - Glass Fiber Reinforced Polyester SMC
- **Antenna Optics**
 - Prime Focus, Offset, 0.6 F/D
- **Mount Type**
 - Elevation over Azimuth
- **Elevation Adjustment Range**
 - 10° to 90° Continuous Fine Adjustment
- **Azimuth Adjustment Range**
 - 360° Continuous, +/- 10° Fine Adjustment
- **Mast Pipe Interface**
 - 2.5 SCH Pipe (2.88" OD) or 3.00" OD (73 or 76mm)
- **Max RF Equipment Weight**
 - Tier 1 Feed Support = 8 lb. (3.6 kg)

Environmental Performance

- **Wind Loading**
 - Operational = 45 mi/h (72 km/h)
 - Survival = 125 mi/h (200 km/h)
- **Temperature**
 - Operational = -40° to 140° F (-40° to 60° C)
 - Survival = -50° to 160° F (-46° to 71° C)
- **Rain**
 - Operational = 1/2"/h (13mm/h)
 - Survival = 2"/h
- **Ice**
 - Survival = ½ inch (13mm) Radial Ice
- **Atmospheric Conditions**
 - Salt, Pollutants, and Contaminants as Encountered in Coastal and Industrial Areas
- **Solar Radiation**
 - 360 BTU/h/ft2 (1135 W/m2)



Satcom & Antenna Technologies Division
1700 NE Cable Drive
Conover, NC
USA 28613

tel +1 770-689-2040
1 888-874-7646 (In North America)
1 619-240-8480 (Outside North America)
email CustomerCareSAT@cpil.com
web www.cpii.com

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI.

D-SATCOM_1.2Ku-Band1122-01-0919