

X LNB 7.90 - 8.50 GHz 1 Band SATCOM TLT

Key features




- Very Low Noise Figure
- Excellent Input VSWR
- High P1dB and IP3
- Low Phase noise meets DVB-S2X profile.
- Wide operating temperature range
- Compact size and light weight



Description

The professional X-Band PLL LNB comes standard with Low Phase Noise to meet DVB-S2X Professional services. The LNB features VERY LOW input VSWR to avoid the need of an external isolator. The X-band PLL LNB model 6.95 cover the frequency range 7.90 to 8.50 GHz with standard gain of 0 dB typ. or gain by request.

Available with Internal LO ref. or with External 10 MHz ref. input. Optional you can order this LNB with CPR 112G adapter.



With optional CPR 112G adapter



Explore our full
product range
in this category



X LNB 7.90 - 8.50 GHz 1 Band SATCOM TLT

Technical specifications

	MODEL/LO	6.95
	Input freq. GHz	7.90 - 8.50 GHz
	Input	WR 112 / R 84. Flange PBR 84
INPUT	Pressurizable	0.1 bar max. (option)
	Input max power	0 dBm instantaneous (not continuous)
	DC Input	+12 to +24 V supplied through output connector
	Current drain	190 mA @ +13 V, 160 mA @ +15 V, 140 mA @ +18 V, 110 mA @ +24 V
	Input VSWR	1.5:1 max.
INTERNAL	LO ref.	Internal or External 10 MHz ref. Note! Different models
	MODELS with External LO ref.	Sine Wave, Level -10 to +10 dBm. Supplied through output connector. With no ext 10 MHz ref. signal present LO shifts -20 ppm.
	MODELS with Internal LO ref.	±0.5 ppm -20 to +70°C (±1 ppm -40 to +80°C), ±1 ppm -20 to +70°C (±1.5 ppm -40 to +80°C)
	LO Leakage	-60 dBm max. @ waveguide input
	Gain	0 dB typ. as standard or by request.
	Flatness	±0.4 dB within 30 MHz, ±2 dB max. over band
	Noise figure	19.90 dB / 28000K @ 0dB gain max.
	Phase Noise	-35 dBc @ 10 Hz -65 dBc @ 100 Hz -85 dBc @ 1 kHz -90 dBc @ 10 kHz -100 dBc @ 100 kHz -128 dBc @ >1 MHz typ.
	Group delay	± 1ns max.
	Out of band rejection	20 dB min.
	Image Rejection	60 dB min.
OUTPUT	IF output	950-1550 MHz
	Output P1dB	+5 dBm typ.
	Output IP3	+15 dBm typ.
	Output VSWR	1.7:1 max. @ 50 ohm
	Output Connector	N-type 50Ω , SMA-type 50Ω or F-type 75Ω
GENERAL	Dimensions	130 x 56 x 51 mm (F- & SMA-connector), 135 x 56 x 51 mm (N-connector)
	Weight	353 g WR112, 420 g CPR112G (F- & SMA-connector) 369 g WR112, 446 g CPR112G (N-connector)
	MTBF	MTBF as per MIL-HDBK-217F Notice 2: Environmental Condition GF (Ground Fixed): >489000 hours, Environmental Condition A1C (Airborne, Inhabited, Cargo): >245000 hours, Quality level: Commercial, Temp used for MTBF calculation: +35 C Ambient
	Temperature range	Storage and operating: -40 to +80°C, -40 to +176° F
	Miscellaneous	Enclosed conductive O-ring, mounting screws (M4 x 10) 4 pcs
OPTIONS	Options	Separate SMA connector for DC input or Ext. 10 MHz reference Customized gain CPR 112 G flange adaptor Extended IF

C-BAND

X-BAND

KU-BAND

KA-BAND

Q/V-BAND

RFoFIBER


L-BAND

EXT REF


OTHER

X LNB 7.90 - 8.50 GHz 1 Band SATCOM TLT

Technical Drawing



With optional CPR112G adaptor



Professional Satcom Frequency Converters & Components. All products are fully CE and RoHS compliant and every unit includes full documentation of performance tests and quality control. Please contact sales@smw.se to configure or customize the unit to your needs. Visit smw.se or scan QR code to see our full product range and request a quote.

