


THIS DRAWING IS A SOURCE CONTROL DRAWING AND IS PROPRIETARY TO MICROWAVE FILTER CO., INC. AND MAY NOT BE DUPLICATED OR DISTRIBUTED WITHOUT WRITTEN PERMISSION OF MICROWAVE FILTER CO., INC. THIS DRAWING ALSO DESCRIBES TRADE SECRETS AND IS THE EXCLUSIVE PROPERTY OF MICROWAVE FILTER CO., INC

REVISION			
LTR	ECN	DATE	APPR'D



SPECIFICATIONS

PASSBAND: 3760-4200 MHz

INSERTION LOSS: 0.5 dB APPROX. @ F_0

0.5 dB APPROX. ROLL OFF @ BAND EDGES

VSWR: 1.44:1 TYP

GROUP DELAY VARIATION: 8 nS MAX

REJECTION

	FREQUENCY
45 dB MIN	3710, 4320 MHz
60 dB TYP	3610, 4430 MHz
70 dB TYP	3570, 4470 MHz
80 dB TYP	5825-7250 MHz
50 dB TYP	7250-7750 MHz

FLANGES: CPR229G (INPUT)

CPR229F (OUTPUT)

HALF GASKET SUPPLIED WITH EACH UNIT

WEIGHT: 1.125 lbs APPROX.

ENVELOPE DRAWING

UNLESS SPECIFIED
ALL TOLERANCES $\pm .060$

MFC MICROWAVE FILTER CO. INC. 6743 KINNE ST. E. SYRACUSE, N.Y. 13057		FSCM27834	
DATE 12/30/13	TITLE BANDPASS FILTER		
DWN BY MW	DRAWING NO. 13961W-3760/4200		REV —
ENGINEER B.P.			