

Innovative Communication Solutions

9500HIBCF

9500 Dual-Band Ka-Band PLL LNB

Frequency: BC: 19.2 - 20.2 | 20.2 - 21.2 GHz

W/G Isolator: Yes

Output Connector: F: 75 Ohm









KEY SPECIFICATIONS

Band Ka-Band 19.20 - 20.20 GHz Input Frequency Band 1 Input Frequency Band 2 20.20 - 21.20 GHz LO Frequency 1 18.25 GHz 19.25 GHz LO Frequency 2 ±50 kHz LO Stability PLL LO Type **Noise Figure Max** 1.6 dB **Noise Figure Typ** 1.5 dB **Number Of Onboard Los** Dual-Band Output Frequency Band 1 950 - 1950 MHz **Output Frequency Band 2** 950 - 1950 MHz

RF SPECIFICATIONS

Control Signal 1 13V / No Tone **Control Signal 2** 18V / No Tone **Conversion Gain Max** 65 dB 55 dB **Conversion Gain Min** 60 dB **Conversion Gain Typ** Gain Flatness (over Full Band) ≤ 5 dB p-p Input VSWR 1.5:1 max. Output P1db + 5 dBm min. **Output VSWR** 2.3:1 max.





Innovative Communication Solutions

Phase Noise 100khz Offset Max -95 dBc/Hz

ELECTRICAL SPECIFICATIONS

Power Requirements +12 to +24V DC

INTERFACE SPECIFICATIONS

IF Connector F-Connector

Isolator With Isolator

RF Input Connector WR-42 waveguide grooved

ENVIRONMENTAL SPECIFICATIONS

IP Rating IP 67

Temperature Operational -40 to +60°C
Temperature Storage -40 to +80°C

PHYSICAL SPECIFICATIONS


Product Height45 mmProduct Length141.8 mmProduct Weight0.465 kgProduct Width60 mm

LOGISTICS SPECIFICATIONS

HS Code Country of Origin Ex Works ECCN Number Unit Package

Made in Korea Richmond, BC, Canada EAR99 118 mm x 60 mm x 45 mm | 0.4 kg

HOW TO ORDER



MECHANICAL DIAGRAMS





Innovative Communication Solutions

