

ULC-2S-50S-6

Universal LNB Controller 6-Band

Reference: 2S: 10 MHz Injection Port; SMA Connector

Connector Type: SMA: 50 Ohm

Control Switch Control & Damp; Line Length Interface Option: Compensation with Switch

 ϵ



KEY SPECIFICATIONS

Control Signal Switch Control & Line Length Compensation with Switch

Reference Signal 10MHz injection port with SMA Female Connector

Tone Amplitude $0.55 \sim 0.9 \text{ vpp}$ Tone Frequency $20 \sim 24 \text{ kHz}$

ELECTRICAL SPECIFICATIONS

Current Consumption500 mA max.Output Current500 mA max.Power Requirements+23 to +25 V DC

INTERFACE SPECIFICATIONS

Connector SMA Connector

Control Interface Switch Control & Line Length Compensation with Switch

LLC Line Length Compensation +1 VDC (Switch)

RF Input Connector 50 Ohm SMA Connector

ENVIRONMENTAL SPECIFICATIONS

IP Rating IP 65

Temperature Operational -40°C to +60°C

PHYSICAL SPECIFICATIONS

Product Height 30 mm

Product Length 100 mm

Product Weight 0.67 kg






Product Width 120 mm

LOGISTICS SPECIFICATIONS


HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8517690000	Made in the Republic of Korea	Richmond, BC, Canada	EAR99	1

HOW TO ORDER




MECHANICAL DIAGRAMS

10 MHz injection port, SMA connector (Switch Control)






10 MHz reference (Switch Control)






No reference or 10 MHz reference (Control Interface Cable)







10 MHz injection port, SMA connector (Control Interface Cable)






No reference (Switch Control)







UNIT : mm

