

Power Divider, 8-way, 20-3000 MHz, SMA Female

ESAT-8PD203000MS

Description

The model is an 8-way splitter covering the band 20MHz to 3GHz in one unit. Enclosure is a rugged aluminum housing. The recessed cover design minimizes RF leakage. Designed, assembled and tested in the USA.




Photo is representative.

Specifications	Min.	Typ.	Max.	Units
Frequency	20	--	3000	MHz
Impedance	--	50	--	Ohm
Return Loss (Port S)	9.5	13.4	--	dB
Return Loss (Port 1-8)	9.5	13.7	--	dB
Insertion Loss (above 9.03dB)	--	4.1	5.7	dB
Isolation	14.0	19.3	--	dB
Amplitude Balance ($\pm$)	--	0.45	0.80	dB
Input Power (CW) ¹	--	--	1	W

Mechanical



Connector Interface	SMA-Female
Operating Temperature ²	-55 to +85 °C
Storage Temperature	-55 to +100 °C
Weight Estimate	6 oz (170 g)
Humidity	10-90% non-condensing
Environment	Indoors Use Only
CAGE Code	87MG8


Materials

RoHS Compliant ³	Yes
REACH Compliant ³	Yes
Enclosure	Aluminum
Connectors	Brass, Gold Plated
Contacts	Be Cu, Gold Plated
Insulators	PTFE
Finish	Clear Chemical Film

1. All output ports should be terminated in a 50-ohm load with 1.2:1 max VSWR.
2. Electrical specifications at +25 °C only.
3. To the best of our knowledge at the time of publication.

Typical Performance at +25 °C






Typical Performance Data

Frequency (MHz)	Return Loss (dB)				Total Loss (dB)			Isolation (dB)		
	Port S	Port 1	Port 4	Port 8	S-1	S-4	S-8	1-2	1-4	1-8
10.0	11.69	15.94	15.66	14.49	10.64	10.64	10.62	27.07	36.91	38.90
22.5	13.99	20.14	19.81	19.76	10.36	10.35	10.35	29.54	40.60	40.51
35.0	14.86	21.55	21.21	21.88	10.27	10.26	10.27	31.16	41.03	40.32
47.4	15.26	22.01	21.68	22.57	10.25	10.23	10.24	32.09	40.78	39.97
59.9	15.48	22.18	21.89	22.79	10.24	10.22	10.23	32.51	40.38	39.83
72.4	15.64	22.24	21.98	22.82	10.24	10.21	10.23	32.73	40.09	39.70
84.9	15.75	22.25	22.00	22.77	10.23	10.21	10.23	32.75	39.66	39.64
97.3	15.85	22.31	22.04	22.79	10.24	10.21	10.23	32.66	39.32	39.64
110	15.96	22.43	22.16	22.87	10.25	10.22	10.25	32.51	39.01	39.62
210	16.48	22.93	22.44	23.11	10.32	10.28	10.33	29.89	36.34	39.68
309	17.01	23.12	22.53	23.32	10.38	10.34	10.41	27.51	34.03	39.78
409	17.60	23.12	22.57	23.49	10.46	10.42	10.48	25.60	32.15	39.44
509	18.23	22.72	22.50	23.33	10.55	10.50	10.57	24.17	30.61	38.67
609	18.85	22.08	22.35	22.89	10.64	10.58	10.65	23.10	29.47	37.61
709	19.39	21.34	22.13	22.27	10.73	10.66	10.73	22.42	28.57	36.45
808	19.86	20.76	21.88	21.73	10.80	10.73	10.79	22.10	28.01	35.45
908	20.34	20.32	21.60	21.22	10.86	10.78	10.84	22.04	27.76	34.69
1008	20.95	20.07	21.28	20.93	10.89	10.81	10.87	22.18	27.75	34.06
1507	23.44	20.59	18.70	21.42	10.92	10.99	10.99	22.83	28.86	33.83
2006	14.59	17.11	15.62	17.49	11.45	11.69	11.62	20.71	25.49	35.71
2505	12.38	14.07	14.79	14.32	11.78	12.20	11.95	20.10	21.33	35.55
3004	15.60	16.13	15.52	16.18	12.34	12.51	12.39	21.20	18.92	33.07
3503	20.01	13.21	13.80	13.33	12.53	12.64	12.64	19.96	17.30	30.53

Outline Dimensions



Outline drawing: OL-8034

Dimensions are in inches, [mm] shown for convenience.

Tolerances on 2-pl decimals: $\pm .03$. 3-pl decimals: $\pm .015$.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or documentation of the part, in order to implement improvements. Esatcom Inc. reserves the right to make such changes as required without notice. Unless otherwise stated, all specifications and dimensions are nominal. Esatcom Inc. does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Esatcom Inc. does not assume any liability arising out of the use of any part of documentation. This document gives only a description of the product(s) and shall not form part of any contract. Please contact a Esatcom Inc. Applications Engineer for the most current specification drawing.