

# 2107HUAN

## 2000 Quad-Band Ku-Band PLL LNB (0.7 dB)

**Frequency:** A: 10.70 - 11.20 GHz | 11.20 - 11.70 GHz | 11.70  
- 12.25 GHz | 12.25 - 12.75 GHz

**L.O. Stability:** +/- 10 kHz

**Output Connector:** N: 50 Ohm



## KEY SPECIFICATIONS

|                         |                   |
|-------------------------|-------------------|
| Band                    | Ku-Band           |
| Input Frequency Band 1  | 10.70 - 11.20 GHz |
| Input Frequency Band 2  | 11.20 - 11.70 GHz |
| Input Frequency Band 3  | 11.70 - 12.25 GHz |
| Input Frequency Band 4  | 12.25 - 12.75 GHz |
| LO Frequency 1          | 9.75 GHz          |
| LO Frequency 2          | 10.25 GHz         |
| LO Frequency 3          | 10.75 GHz         |
| LO Frequency 4          | 11.30 GHz         |
| LO Stability            | ±10 kHz           |
| LO Type                 | PLL               |
| Noise Figure Max        | 0.8 dB            |
| Noise Figure Typ        | 0.7 dB            |
| Number Of Onboard Los   | Quad-Band         |
| Output Frequency Band 1 | 950 - 1450 MHz    |
| Output Frequency Band 2 | 950 - 1450 MHz    |
| Output Frequency Band 3 | 950 - 1500 MHz    |
| Output Frequency Band 4 | 950 - 1450 MHz    |
| Tone Frequency          | 22 kHz ± 4 kHz    |

## RF SPECIFICATIONS

|                  |                  |
|------------------|------------------|
| Control Signal 1 | 13V / No Tone    |
| Control Signal 2 | 13V / 22kHz Tone |

## Innovative Communication Solutions

|                                |                  |
|--------------------------------|------------------|
| Control Signal 3               | 18V / No Tone    |
| Control Signal 4               | 18V / 22kHz Tone |
| Conversion Gain Max            | 65 dB            |
| Conversion Gain Min            | 55 dB            |
| Conversion Gain Typ            | 60 dB            |
| Gain Flatness (over Full Band) | ≤ 6 dB p-p       |
| Input VSWR                     | 2.3 : 1 max.     |
| Output P1db                    | + 5 dBm min.     |
| Output VSWR                    | 2.2 : 1 max.     |
| Phase Noise 0.1kHz Offset Max  | -125 dBc/Hz      |

## ELECTRICAL SPECIFICATIONS

|                     |                |
|---------------------|----------------|
| Current Consumption | 350 mA max     |
| Power Requirements  | +12 to +24V DC |

## INTERFACE SPECIFICATIONS

|                    |                         |
|--------------------|-------------------------|
| IF Connector       | N-Connector             |
| RF Input Connector | WR-75 waveguide grooved |

## ENVIRONMENTAL SPECIFICATIONS

|                         |                |
|-------------------------|----------------|
| Humidity                | 0 - 95%        |
| IP Rating               | IP 66          |
| Temperature Operational | -40°C to +70°C |
| Temperature Storage     | -50 to +80°C   |

## PHYSICAL SPECIFICATIONS

|                |          |
|----------------|----------|
| Product Height | 1.70 in  |
| Product Length | 4.46 in  |
| Product Weight | 0.255 kg |
| Product Width  | 1.72 in  |

## LOGISTICS SPECIFICATIONS

| HS Code | Country of Origin | Ex Works             | ECCN Number | Unit Package                   |
|---------|-------------------|----------------------|-------------|--------------------------------|
|         | Made in Canada    | Richmond, BC, Canada | EAR99       | 135 x 68 x 48 mm  <br>0.335 kg |

## HOW TO ORDER



### 2108HSAF

|              |               |                                                                         |
|--------------|---------------|-------------------------------------------------------------------------|
| LNB SERIES # | CONNECTOR     | F: 75 Ohm<br>N: 50 Ohm                                                  |
|              | FREQUENCY     | A / B / C / D / E / F / G<br>(Please see next page for frequency bands) |
|              | BAND          | S: Single-Band<br>D: Dual-Band<br>T: Triple-Band<br>U: Quad-Band        |
|              | REFERENCE     | H: Internal Reference<br>X: External Reference                          |
|              | NOISE FIGURE  | 7: 0.7 dB<br>8: 0.8 dB<br>9: 0.9 dB                                     |
|              | L.O STABILITY | 0: External Reference<br>1: ±10 kHz<br>2: ±25 kHz                       |

## MECHANICAL DIAGRAMS


### FREQUENCY BANDS

| Single Band |               |               |                |                | Dual Band                                                                                    |               |               |                |                |                |               |
|-------------|---------------|---------------|----------------|----------------|----------------------------------------------------------------------------------------------|---------------|---------------|----------------|----------------|----------------|---------------|
| Band        | RF freq (GHz) |               | L.O freq (GHz) | Output freq    | Band                                                                                         | RF freq (GHz) |               | L.O freq (GHz) | Output freq    | Voltage/Tone   |               |
| A           | 11.7 - 12.20  |               | 10.75          | 950 - 1450 MHz | A                                                                                            | Band 1        | 10.95 - 11.70 | 10             | 950 - 1700 MHz | 13 V           |               |
| B           | 12.25 - 12.75 |               | 11.3           | 950 - 1450 MHz |                                                                                              | Band 2        | 11.70 - 12.75 | 10.75          | 950 - 2000 MHz | 18 V           |               |
| C           | 10.95 - 11.70 |               | 10             | 950 - 1700 MHz | B                                                                                            | Band 1        | 10.70 - 11.70 | 9.75           | 950 - 1950 MHz | 13 V           |               |
| D           | 10.70-11.80   |               | 9.75           | 950 - 2050 MHz |                                                                                              | Band 2        | 11.70 - 12.75 | 10.75          | 950 - 2000 MHz | 18 V           |               |
| Triple Band |               |               |                |                | C <td>Band 1</td> <td>10.70 - 11.70</td> <td>9.75</td> <td>950 - 1950 MHz</td> <td>13 V</td> | Band 1        | 10.70 - 11.70 | 9.75           | 950 - 1950 MHz | 13 V           |               |
| Band        | RF freq (GHz) |               | L.O freq (GHz) | Output freq    |                                                                                              | Voltage/Tone  | Band 2        | 11.70 - 12.75  | 10.75          | 950 - 2000 MHz | 18 V          |
| A           | Band 1        | 10.95 - 11.70 | 10             | 950 - 1700 MHz | 13 V                                                                                         | D             | Band 1        | 10.95 - 11.70  | 10             | 950 - 1700 MHz | 13 V          |
|             | Band 2        | 11.70 - 12.20 | 10.75          | 950 - 1450 MHz | 13 V / 22 kHz                                                                                |               | Band 2        | 12.25 - 12.75  | 11.3           | 950 - 1450 MHz | 18 V          |
|             | Band 3        | 12.20 - 12.75 | 11.25          | 950 - 1500 MHz | 18 V                                                                                         | D             | Band 1        | 10.70 - 11.70  | 9.75           | 950 - 1950 MHz | 13 V          |
| B           | Band 1        | 10.95 - 11.70 | 10             | 950 - 1700 MHz | 13 V                                                                                         |               | Band 2        | 11.70 - 12.25  | 10.75          | 950 - 1500 MHz | 13 V / 22 kHz |
|             | Band 2        | 11.70 - 12.25 | 10.75          | 950 - 1500 MHz | 13 V / 22 kHz                                                                                | Band 3        | 12.25 - 12.75 | 11.3           | 950 - 1450 MHz | 18 V           |               |
|             | Band 3        | 12.25 - 12.75 | 11.3           | 950 - 1450 MHz | 18 V                                                                                         | Quad Band     |               |                |                |                |               |
| C           | Band 1        | 10.70 - 11.70 | 9.75           | 950 - 1950 MHz | 13 V                                                                                         | Band          | RF freq (GHz) |                | L.O freq (GHz) | Output freq    | Voltage/Tone  |
|             | Band 2        | 11.70 - 12.20 | 10.75          | 950 - 1450 MHz | 13 V / 22 kHz                                                                                | A             | Band 1        | 10.70 - 11.20  | 9.75           | 950 - 1450 MHz | 13 V          |
|             | Band 3        | 12.20 - 12.75 | 11.25          | 950 - 1500 MHz | 18 V                                                                                         |               | Band 2        | 11.20 - 11.70  | 10.25          | 950 - 1450 MHz | 13 V / 22 kHz |
| D           | Band 1        | 10.70 - 11.70 | 9.75           | 950 - 1950 MHz | 13 V                                                                                         |               | Band 3        | 11.70 - 12.25  | 10.75          | 950 - 1500 MHz | 18 V          |
|             | Band 2        | 11.70 - 12.25 | 10.75          | 950-1500 MHz   | 13 V / 22 kHz                                                                                |               | Band 4        | 12.25 - 12.75  | 11.3           | 950 - 1450 MHz | 18 V / 22kHz  |
|             | Band 3        | 12.25 - 12.75 | 11.3           | 950-1450 MHz   | 18 V                                                                                         | B             | Band 1        | 10.70 - 10.95  | 9.75           | 950 - 1200 MHz | 13 V          |
| E           | Band 1        | 10.95 - 11.70 | 10             | 950 - 1700 MHz | 13 V                                                                                         |               | Band 2        | 10.95 - 11.70  | 10             | 950 - 1700 MHz | 13 V / 22 kHz |
|             | Band 2        | 11.55 - 12.25 | 10.6           | 950 - 1650 MHz | 13 V / 22 kHz                                                                                |               | Band 3        | 11.70 - 12.25  | 10.75          | 950 - 1500 MHz | 18 V          |
|             | Band 3        | 12.20 - 12.70 | 11.25          | 950 - 1450 MHz | 18 V                                                                                         |               | Band 4        | 12.25 - 12.75  | 11.3           | 950 - 1450 MHz | 18 V / 22kHz  |
| F           | Band 1        | 10.70 - 11.80 | 9.75           | 950 - 2050 MHz | 13 V                                                                                         | C             | Band 1        | 10.70 - 11.20  | 9.75           | 950 - 1450 MHz | 13 V          |
|             | Band 2        | 10.95 - 12.10 | 10             | 950 - 2100 MHz | 13 V / 22 kHz                                                                                |               | Band 2        | 11.20 - 11.70  | 10.25          | 950 - 1450 MHz | 13 V / 22 kHz |
|             | Band 3        | 11.70 - 12.75 | 10.75          | 950 - 2000 MHz | 18 V                                                                                         |               | Band 3        | 11.70 - 12.20  | 10.75          | 950 - 1450 MHz | 18 V          |
| G           | Band 1        | 10.70 - 11.70 | 9.75           | 950 - 1950 MHz | 13 V                                                                                         |               | Band 4        | 12.20 - 12.75  | 11.25          | 950 - 1500 MHz | 18 V / 22kHz  |
|             | Band 2        | 11.70 - 12.70 | 10.75          | 950 - 1950 MHz | 13 V / 22 kHz                                                                                | D             | Band 1        | 10.95 - 11.45  | 10             | 950 - 1450 MHz | 13 V          |
|             | Band 3        | 12.25 - 12.75 | 11.3           | 950 - 1450 MHz | 18 V                                                                                         |               | Band 2        | 11.45 - 11.95  | 10.5           | 950 - 1450 MHz | 13 V / 22 kHz |
|             |               |               |                |                |                                                                                              | Band 3        | 11.70 - 12.20 | 10.75          | 950 - 1450 MHz | 18 V           |               |
|             |               |               |                |                |                                                                                              | Band 4        | 12.20 - 12.75 | 11.25          | 950 - 1500 MHz | 18 V / 22kHz   |               |



Norsat  
International Inc.

Innovative Communication Solutions



Esatcom Inc  
Norsat authorized distributor  
[www.esatcom.com](http://www.esatcom.com)

Tel  
718.799.0084

Email  
[sales@esatcom.com](mailto:sales@esatcom.com)