



1208HEF

1000 Ku-Band Single Band PLL LNB

L.O Stability: 2: ± 25 kHz

Output Connector: F: 75 Ohm



KEY SPECIFICATIONS

Band	Ku-Band
Input Frequency Band 1	10.95 - 12.75 GHz
LO Frequency 1	10.00 GHz
LO Stability	± 25 kHz
LO Type	PLL
Noise Figure Max	1.0 dB
Noise Figure Typ	0.8 dB
Number Of Onboard Los	Single-Band
Output Frequency Band 1	950 - 2750 MHz

RF SPECIFICATIONS

Conversion Gain Max	65 dB
Conversion Gain Min	50 dB
Conversion Gain Typ	55 dB
Gain Flatness (over Full Band)	≤ 6 dB p-p
Input VSWR	2.5 : 1 max.
Output P1db	+ 3 dBm min.
Output VSWR	2.2 : 1 max.
Phase Noise 100kHz Offset Max	-90 dBc/Hz

ELECTRICAL SPECIFICATIONS

Current Consumption	350 mA max.
Power Requirements	+12 to +24V DC

INTERFACE SPECIFICATIONS

IF Connector	F-Connector
RF Input Connector	WR-75 waveguide grooved



M and C SPECIFICATIONS

Led Indicators None

ENVIRONMENTAL SPECIFICATIONS

IP Rating IP 67
Temperature Operational -40°C to +60°C
Temperature Storage -40 to +80°C


PHYSICAL SPECIFICATIONS

Product Height 42 mm
Product Length 130 mm
Product Weight 0.4 kg
Product Width 60 mm

LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8517690000	Made in the Republic of Korea	Richmond, BC, Canada	EAR99	145 x 95 x 65 mm

HOW TO ORDER



MECHANICAL DIAGRAMS

