

1009XHBF

1000 Ku-Band Single Band EXT REF LNB

Noise Figure: 0.9 dB

Frequency: B: 12.25 - 12.75 GHz

Output Connector: F: 75 Ohm



KEY SPECIFICATIONS

Band	Ku-Band
External Ref Freq	10 MHz (sine-wave), - 10 to 0 dBm
Input Frequency Band 1	12.25 - 12.75 GHz
LO Frequency 1	11.30 GHz
LO Stability	Ext Ref
LO Type	EXT
Noise Figure Max	1.0 dB
Noise Figure Typ	0.9 dB
Number Of Onboard Los	Single-Band
Output Frequency Band 1	950 - 1450 MHz

RF SPECIFICATIONS

Conversion Gain Max	65 dB
Conversion Gain Min	55 dB
Conversion Gain Typ	60 dB
Gain Flatness (over Full Band)	≤ 4 dB p-p
Input VSWR	2.5 : 1 max.
Output P1db	+ 5 dBm min.
Output VSWR	2.0 : 1 max.
Phase Noise 1khz Offset Max	Phase Locked to External Reference
Phase Noise 10khz Offset Max	Phase Locked to External Reference
Phase Noise 100khz Offset Max	Phase Locked to External Reference

ELECTRICAL SPECIFICATIONS

Current Consumption	300 mA
Power Requirements	+15 to +24V DC

INTERFACE SPECIFICATIONS

IF Connector	F-Connector
--------------	-------------

RF Input Connector

WR-75 waveguide grooved

M and C SPECIFICATIONS

Led Indicators

None

ENVIRONMENTAL SPECIFICATIONS

Temperature Operational

-40 to +60°C

Temperature Storage

-40 to +80°C

PHYSICAL SPECIFICATIONS

Product Height

42 mm

Product Length

110 mm

Product Weight

0.3 kg

Product Width

42 mm

LOGISTICS SPECIFICATIONS

HS Code

Country of Origin

Ex Works

ECCN Number

Unit Package

8517690000


Made in the Republic of
Korea

Richmond, BC, Canada

EAR99

140 x 50 x 50 mm |

HOW TO ORDER




MECHANICAL DIAGRAMS



Norsat
International Inc.

Innovative Communication Solutions



Norsat
International Inc.

ESATCOM
INC

Norsat authorized distributor

Esatcom Inc.

3628 Francis Lewis Blvd.

Flushing, NY 11358

www.esatcom.com

Tel: 718.799.0084

Email: sales@esatcom.com