



RSLNBXSKA12T3


LNB Redundant Switch System

Single-Band 1:2

Component: LNBXS = LNB External Ref Single-Band

Band: Ka-Band

Tx/Rx Config + IFL Length: Tx/Rx + 30m IFL



[Explore Video Course](#)



KEY SPECIFICATIONS

Band	Ka-Band
Redundancy	1:2
Switchover Time	120 ms max.

RF SPECIFICATIONS

Input VSWR	LNB Dependent
Insertion Loss	0.5 dB max.

ELECTRICAL SPECIFICATIONS

Power	90 - 264 VAC (47 - 63 Hz)
-------	---------------------------

INTERFACE SPECIFICATIONS

Component	LNB, External Ref, Single Band
IFL Cable Length	30m
RF Input Connector	Ka-Band: WR-42
RF Output Connector	N-Connector
Tx Rx Configuration	Tx / Rx

ENVIRONMENTAL SPECIFICATIONS



Relative Humidity	< 100%
Temperature Operational	-40°C to +60°C

PHYSICAL SPECIFICATIONS


Product Height	295 mm
Product Length	483 mm
Product Weight	9 kg
Product Width	159 mm

LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8517690000	Made in Canada	Richmond, BC, Canada	EAR99	584 x 661 x 686 mm 54.8 kg

HOW TO ORDER

RSLNBISKU11R3



MECHANICAL DIAGRAMS



Norsat
International Inc.

Innovative Communication Solutions



ESATCOM
INC

Norsat authorized distributor

Esatcom Inc.

3628 Francis Lewis Blvd.

Flushing, NY 11358

www.esatcom.com

Tel: 718.799.0084

Email: sales@esatcom.com