

RSLNBKA11NIMP

LNB Redundant Switch System 1:1


Band: Ka-Band

Connector Type: N-Connector Output

Options: 10 MHz Injection via SMA + Boom Mount + Power Supply Connector

*Mating power connector is available as a standard optional.

Supported LNBs: N-conn LNBs up to Quad-band and non simultaneous-band. **Sold separately.**



[Explore Video Course](#)



KEY SPECIFICATIONS

Band	Ka-Band
Input Frequency Band 1	950 - 2150 MHz
Redundancy	1:1
Switchover Time	420 ms max.

RF SPECIFICATIONS

Insertion Loss	Waveguide to LNB: 0.5 dB max.; LNB to Cable: 2.8 dB max.
-----------------------	--

ELECTRICAL SPECIFICATIONS

Power	100-240 VAC (50-60 Hz)
--------------	------------------------

INTERFACE SPECIFICATIONS

Input Connector	WR-42
RF Output Connector	N-Connector

ENVIRONMENTAL SPECIFICATIONS



Innovative Communication Solutions

IP Rating	IP 66
Relative Humidity	Operational: 8% - 100%; Storage: 10% - 100%
Temperature Operational	-40°C to +60°C
Temperature Storage	-50 to +80°C

PHYSICAL SPECIFICATIONS


Controller Box Height	66.80 mm
Controller Box Length	411.73 mm
Controller Box Weight	3.4 kg
Controller Box Width	163.83 mm
RF Switch Height	106.93 mm
RF Switch Length	158.87 mm
RF Switch Weight	0.53 kg
RF Switch Width	53.70 mm

LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8517690000	Made in Canada	Richmond, BC, Canada	EAR99	501.65 x 393.70 x 311.15 mm 8.16 kg

HOW TO ORDER

RSLNBKU11NRMP





MECHANICAL DIAGRAMS



Norsat
International Inc.

Innovative Communication Solutions

1:1 Switch



Norsat
International Inc.

ESATCOM
INC

Norsat authorized distributor

Esatcom Inc.

3628 Francis Lewis Blvd.

Flushing, NY 11358

www.esatcom.com

Tel: 718.799.0084

Email: sales@esatcom.com