

# BT-1222

## Bias Tee BT-1200 Series

**DC Connector:** 2: F (Female) - 75 Ohm

**10 MHz Injection:** 2: F (Female) - 75 Ohm



## KEY SPECIFICATIONS

Band	L-Band
Pass Band	950 - 1450 MHz

## RF SPECIFICATIONS

10mhz Pass Band	10 - 100 MHz
Input VSWR	2.0 : 1 max.
Insertion Loss Max	1 dB
Output VSWR	2.0 : 1 max.

## INTERFACE SPECIFICATIONS

10mhz Injection	F (Female) - 75 Ohm
DC Connector	F (Female) - 75 Ohm
Output Connector	F (Female) - 75 Ohm
RF Input Connector	N (Female) - 50 Ohm

## ENVIRONMENTAL SPECIFICATIONS

IP Rating	IP 66
Temperature Operational	-30°C to +50°C
Temperature Storage	-40 to +70°C

## PHYSICAL SPECIFICATIONS

Product Height	25 mm
Product Length	105 mm
Product Weight	0.17 kg




Product Width 55 mm

### LOGISTICS SPECIFICATIONS

HS Code	Country of Origin	Ex Works	ECCN Number	Unit Package
8517690000	Made in Canada	Richmond, BC, Canada	EAR99	105 x 55 x 25 mm

### HOW TO ORDER

#### BT-1188






### MECHANICAL DIAGRAMS



**Norsat**  
International Inc.

Innovative Communication Solutions



**n** | Norsat  
International Inc.

**ESATCOM**  
INC.

Norsat authorized distributor

**ESATCOM INC.**  
3628 Francis Lewis Blvd.  
Flushing, NY 11358  
[www.esatcom.com](http://www.esatcom.com)  
Tel: 718.799.0084  
Email: [sales@esatcom.com](mailto:sales@esatcom.com)