

P7002R

Fully synthesised, Remote Mounted, IF to L-band, Up Converter



The **P7002R** is a remote mounted version of the popular Peak P7002 fully synthesised L-Band up converter which provides a low-cost solution for systems requiring an IF interface at 70MHz $\pm$ 18MHz or 140MHz $\pm$ 36MHz.

For control, the unit incorporates serial communications and an Ethernet interface that support control from a web-page or SNMP network management system. The **FPC100** is offered which is a standard 19-inch rack mount control unit that can interface with up to three **P7002R** units plus the 1+1 or 2+1 redundancy systems. For supply, the unit accepts a wide range of DC voltages, or can be offered with the **OPS27c** AC/DC PSU unit.

For redundancy, the **P7002R** uses a simple CANBUS® interface and integral redundancy controller for 1+1 & 2+1 operation (external **T1000LR**, **T2000LR** switch units are available).

The **P7000 series** of converters are designed to meet the phase noise, spurious, level and frequency stability requirements of Intelsat IBS/ Eutelsat SMS specifications and are compliant with IESS308/ 309. The product is suitable for high order modulation schemes and both very high & low data rates associated with digital TV signals.

The unit has a highly stable internal reference source and will automatically detect and lock to an external 10MHz signal, when applied.

Peak Features

-  Compliant with IESS308/ 309 requirements
-  Suitable for use with latest high order modulation schemes in excess of 100Mbits/sec
-  Integral 1+1 & 2+1 CANBUS® redundancy control & external switch units available
-  Aux DC and 10MHz reference outputs for block up converters
-  Full remote control including Ethernet with embedded web server and SNMP NMS
-  External alarm monitoring for block converters
-  Software trimming of internal 10MHz reference
-  Compact and rugged weatherproof design



P7002R – Typical Specification

IF Input

Frequency	70 ±18MHz
Option 1a;	140 ±36MHz
Connection	50Ω, N-Type (f)

L-band Output

Frequency	950-1525MHz
Option 5;	950-1700MHz
Option 5a;	950-1750MHz
Connection	50Ω, N-type (f)

Transfer Characteristics

Conversion gain	+20dB ±1dB
Attenuation	0 to 30dB, stepped 0.1dB
1 dB GCP	Input -10dBm, output +10dBm
Gain stability	±0.5dB from 0 to 40°C
	±0.1dB per week (constant temp.)
Gain flatness	±1dB full band (±1.5dB for wideband options)
	±0.5dB across any 36MHz in band
Synth resolution	1Hz

RF Performance

Phase noise	-75dBc/Hz at 10Hz
	-85dBc/Hz at 100Hz
	-85dBc/Hz at 1kHz
	-85dBc/Hz at 10kHz
	-97dBc/Hz at 100kHz
	-108dBc/Hz at 1MHz
Harmonics	Better than -50dBc
Spurious	<-65dBm (in band, non-carrier related)
	<-60dBm with option 5 (in band, non-carrier related)
	<-60dBc (in band, carrier related)
Group delay	Linear 0.025ns/MHz
	Ripple 1ns p-p
	Parabolic 0.015ns/MHz ²
Noise figure	20 to 25dB typical at maximum gain

Block Up Converter Drive

Output reference	10MHz at 0dBm nominal
DC supply	+22.5 volts regulated at 0.65 amps
Connection	Fed to BUC on L-band cable
Control	Switchable on/ off

External Reference Input (with automatic detection & locking)

Frequency	Factory selectable 5 or 10MHz
Connection	50Ω, TNC (f)
Level	0dBm ±5dB
Phase noise	to be better than 50dBc/Hz of output phase noise

Internal Back-up Reference

Frequency	10MHz
Adjustment	±0.45ppm, stepped 0.01ppm

Standard Stability

Allan deviation	<5 x 10 ⁻¹² over 1s
Ageing	<±3 x 10 ⁻¹⁰ /day, <±3 x 10 ⁻⁹ /month, <±3 x 10 ⁻⁸ /year
Temp stability	<±2 x 10 ⁻⁹ over operating range

High stability (Option 8)

Allan deviation	<2 x 10 ⁻¹² over 1s
Ageing	<±2 x 10 ⁻¹⁰ /day, <±2 x 10 ⁻⁹ /month, <±2 x 10 ⁻⁸ /year
Temp stability	<±1.5 x 10 ⁻⁹ over operating range

Mechanical

Dimensions	290 x 230 x 95mm (11.4 x 9.1 x 3.7inch)
Construction	Die-cast Aluminium, weatherproof, IP66 rated
Weight	Approx. 4kgs (9lbs)

Environmental

Operating temp	-10°C to +50°C (less solar gain)
Option 12;	-40°C to +50°C (less solar gain), with extended warm-up for cold start operation
Humidity	0-100% condensing
EMC	EN55022, part B & EN50082-1
Safety	EN60950
Power supply	
Voltage	27-36VDC range
Power	35 Watts max.
Connection	multi-pin circular weatherproof (mating part supplied)

Control System

Remote control	RS232/ 485 port
	Ethernet; embedded web server & SNMP network management support.
Redundancy	CANBUS® interface & in-built 1+1 & 2+1 controller
Alarms	Summary failure relay (form C)

Options


- 1a) 140MHz IF Input
- 5) Wide band output 950-1700MHz
- 5a) Wide band output 950-1750MHz
- 8) High stability internal reference option
- 12) Low temperature operation to -40°C
- 16) Factory pre-set IP address

Notes; other 'P7000 series' options do not apply to these products.
The addition of options can modify the typical specification, for details please consult the factory.

Associated products

- OPS27c remote mounted AC/DC PSU
- FPC100 rack mount control panel (1RU)
- T1000LR remote mounted 1+1 redundancy switch unit
- T2000LR remote mounted 2+1 redundancy switch unit

Connector panel view (sample)



ESATCOM INC.

3628 Francis Lewis Blvd.

Flushing, NY 11358

www.esatcom.com

Tel: 718.799.0084

Email: sales@esatcom.com