

Victor Series Switch Matrix/Router

16 x 16 Distributive L-band

VTR-101 is an extended L-band 16x16 distributive matrix in a compact 1U chassis.



RF Parameters					
Capacity		Up to 16 inputs x 16 outputs			
Routing		Distributive, non-blocking		Any input can be connected to any number of outputs	
Frequency Range		850-2450 MHz			
Switching Time		< 50ms (From receipt of a command to implementation of path change)			
RF Connectors		50 Ω SMA	50 Ω BNC	75 Ω BNC	75 Ω F-type
Flatness	Full Band	±1.75 dB	±1.75 dB	±2.0 dB	±2.0 dB
	850-2150 MHz	±1.25 dB	±1.25 dB	±1.5 dB	±1.5 dB
	Any 36 MHz	±0.3 dB	±0.3 dB	±0.5 dB	±0.5 dB
Input Return Loss	Typ.	20 dB	20 dB	14 dB	14 dB
	Min.	14 dB	14 dB	10 dB	8 dB
Output Return Loss	Typ.	20 dB	20 dB	14 dB	14 dB
	Min.	14 dB	14 dB	10 dB	8 dB
Gain	Gain	0 ± 2 dB		Typical, mean across band	
	Gain Control	0 to +5 dB		Settable at each input	
	Gain Steps	0.25 dB			
1 dB GCP	850-2150 MHz	Min. 4 dBm		1 dB Gain Compression point, output power, at Unity Gain	
	2150-2450 MHz	Min. 2 dBm			
OIP3	Full Band	18 dBm typ., 13 dBm min.		At Unity Gain	
	850-2150 MHz	19 dBm typ., 16 dBm min.			
OIP2	Typ.	26 dBm		At Unity Gain	
	Min.	24 dBm		At Unity Gain	
Isolation	I/P - O/P	60 dB		Minimum between any 2 ports	
	I/P - I/P	75 dB		Minimum between any 2 ports	
	O/P - O/P	75 dB		Minimum between any 2 ports	
Group Delay		≤ 1 ns			
Noise Figure	Full Band	Typical 14 dB, max. 17 dB		Unity Gain, with one input routed to one output	
	850-2150 MHz	Typical 13 dB, max. 16dB		Unity Gain, with one input routed to one output	
Input RF Power		+20 dBm		Absolute maximum	
Spurious	Carrier Related	-65 dBc		Excluding harmonics. max. Carrier level -10dBm	
	Carrier Un-related	-85 dBm		With operating frequencies	
Environmental					
Temperature		Operating: 0 to 45°C Storage: -20°C to +75°C			
Location / Humidity		Indoor use only / 20 to 90% non-condensing			
Altitude		10,000 feet AMSL (Operational) 30,000 feet AMSL (Storage)			
Gain Stability vs Temperature		0.05 dB/°C			
Power					
PSU Power		85-264Vac 50-60Hz		Fused 2A	
AC Consumption		20W		Max. consumption at steady state	
PSU		Dual redundant		Diode OR	
MTBF		Chassis: > 250,000		Matrix card: > 100,000	



System Control	
Local Control & Monitoring	HMI
Remote Control & Monitoring	Ethernet via RJ45, 10BaseT/100BaseTx ETL TCP/IP, SNMPv3, HTTPS, Built in Web Server
Alarms	Via Ethernet (RJ45) or HMI
PSU Redundancy	Dual Redundant & Alarmed
Physical	
Dimensions	1U high x 650mm deep x 19" wide
Weight	10 kg
Colour	RAL 9003 semi-matte (white)
Spec. Version	1.3

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

Note 3: Typical parameters are guide figures and measured data may deviate from the quoted figures. ETL endeavours to exceed the quoted typical parameters where practically possible.