



Journey Manpack

The Journey Manpack is the latest in Norsat's series of ultra-portable satellite terminals designed for military and commercial applications. The Journey Manpack is the highest performance "one case" solution in the industry. With IATA compliant packaging and tool-free assembly, the Journey Manpack offers a 0.9m aperture size and provides:

- Unmatched durability
- Maximum portability
- HD video and IP transmission
- 4+ hours continuous runtime with battery pack



Portable and Reliable

The Journey Manpack is a highly integrated complete solution including a compact, segmented antenna system, BUC, LNB, optional modem, comprehensive alignment tools, and a single backpack. The Journey Manpack weighs less than 18 kg (40 pounds) and is ideal for military Special Forces and government applications that require maximum portability.

Intelligent

The Journey Manpack is optionally equipped with Norsat's Satellite Acquisition Assistant (SAA) that provides everything necessary to easily point, peak, and acquire a satellite. Tools included in the SAA package include:

- Spectrum analyzer
- GPS
- Inclinator
- Compass
- Narrow Band Power Meter
- DVB/S2 receiver
- LinkControl software

Tough

The Journey Manpack is MIL-STD-810G compliant and has been built to operate in harsh and hostile environments. All of Norsat's portable satellite terminals are designed for durability and to withstand tough military applications.

Ultra-Portable

- Single Backpack
- Airline Checkable
- Light Weight

Intelligent

- Assisted-Acquire
- Optional 4/6 Cell Battery Pack
- Optional LinkControl Pointing Tools

Easy

- Quick Assembly
- No Tools Required
- Minimal Training Required

JOURNEY MANPACK

System	Ku-Band
G/T (Midband, 20°)	17.3 dB/K
Antenna	0.9m Carbon Fiber, Six segments, Parabolic Single Offset
Tripod	Elevation/Azimuth
Antenna Travel	
Azimuth	+/- 180°
Elevation	10 - 90°
Polarization	+/- 90°
Optional Pointing Tools	

Antenna	Rx	Tx
Frequency	10.70 - 12.75 GHz	13.75 - 14.5 GHz
Midband Gain	39 dBi	40 dBi
Axial Ratio	-	-
Cross-Pol Isolation	<33 dB on axis	

Transmit	
Output Frequency	13.75 - 14.5 GHz
Reference	10 MHz
Reference Level	0 +/- 5 dBm
Gain (typical)	75 dB
Spectral Regrowth	-26dBc @ 46 dBm

Packaging	
Ku-Band System Weight	<14 kg
Backpack	< 4 kg

Environmental	
Operating Temp	-40 to +55 °C
Humidity	100%
Wind Load	36 km/h (free-standing) 65 km/h (anchored)

- | Options |
|--|
| Battery pack (4+ hours runtime) |
| SAA Satellite Acquisition Assistant Pointing Tools & Link Control Software |
| Ruggedized iDirect e800 Outdoor Modem Unit (OMU-800) |



Esatcom Inc
Norsat authorized distributor

Tel
718.276.0800

Email
sales@esatcom.com