

Innovative Communication Solutions

WAYFARER[™] WFM120KU

1.2m Ku-Band Manual Fly-Away

The Norsat WAYFARER[™] commercial 1.2m fly-away antenna is a fast deploying, easy-to-use, and compact SATCOM VSAT. This antenna is an excellent choice for commercial applications in various industries.

The WAYFARER 1.2m fly-away antenna offers excellent rugged and reliable satellite links for remote enterprise, energy, emergency, and media applications.

FEATURES

- · Rugged and lightweight pedestal design
- · Lightweight and durable carbon fiber reflector
- · Fast, simple, tool-free deployment
- · 2-case packing solution
- · Wide range of Norsat BUC and LNB configurations



SPECIFICATIONS

ELECTRICAL

Reflector aperture	1.2m
Reflector material	Carbon fiber
Feed Configuration	Center
Tx Frequency	13.75 to 14.5 GHz
Rx Frequency	10.70 to 12.75 GHz
Tx Gain	42.5+20log(f/14.25) dBi
Rx Gain	41.5+20log(f/12.5) dBi
Polarization	Linear
Cross polarization (On-Axis)	≥35dB
Rx/Tx isolation	Rx > 35dB Tx > 85dB
Sidelobe	First sidelobe < -14 dBi
Azimuth range	±200°
Elevation range	0° to 90°
Polarization range	±90°
Feed interface	WR75

MECHANICAL

Ruggedized w	eatherproof case	
Case 1	Pedestal assembly	Size: 80.2 cm (L) x 52 cm (W) x 31.6 cm (H); Weight: ≤25Kg
Case 2	Reflector / feed	Size: 84.5 cm (L) x 62 cm (W) x 49 cm (H); Weight: ≤24Kg

ENVIRONMENTAL

der or contract

Wind load - operational	36 km/h
Wind load - survival	65 km/h
Temperature	-40°C to +60°C
Humidity	0-95% (20°C)
Water ingress	IP 65 (antenna only)

WAYFARER WFM120KU 1.2M KU-BAND MANUAL FLY-AWAY ANTENNA

HOW TO ORDER

WFM120KU

BUC OPTIONS	BUC	BUC POWER SUPPLY Via IFL Cable Connection Via IFL Cable Connection Via IFL Cable Connection Via IFL Cable Connection Via IFL Cable Connection		BUC M & C CABLE	BUC MOUNTING BRACKETS Not Required Not Required Not Required WFM090KUMT-006 WFM090KUMT-008
2W	ELMTBKU002			Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable	
3W	ELMTBKU003				
4W	ELMTBKU004				
6W	ELMTBKU006				
8W	ELMTBKU008				
10W	ELMTBKU010	Via IFL Cable Co	nnection	Not Applicable	WFM090KUMT-010
16W	ATOMBKU016	PS300-AT1(NA/UK/EU/IEC)		CABLEM+C-AT10	WFM090KUMT-024
20W	ATOMBKU020	PS300-AT1(NA/UI	(/EU/IEC)	CABLEM+C-AT10	WFM090KUMT-024
40W	ATOMBKU040	PS300-AT1(NA/UK/EU/IEC)		CABLEM+C-AT10	WFM090KUMT-024
NB OPTIONS	SERIES				
IB	1000H or HS1000				
L CABLE OPTIONS	NN-FF	NN-NN	FN-NN	FN-FF	FF-FF
L Cable (10m)	IFL-NN-FF-10	IFL-NN-NN-10	IFL-FN-NN-10	IFL-FN-FF-10	IFL-FF-FF-10

WF-INT

Assembly, function verification, and pointing test (standard product/RF packages only)



Esatcom Inc Norsat authorized distributor

Tel 718.276.0800 Email sales@esatcom.com