



ETL Systems

Excelling in RF Engineering

Model Number:


NSN-102-xxxx

32 x 32 Ensign Extended L-band Fan-In-Fan-Out Switch Matrix / Router with

0-10dB variable gain

Typical applications:

- RF content acquisition for TVRO & IPTV headends
- Signal monitoring of satellite traffic
- Remote controlled unmanned satcom sites



Switching flexibility

with the ability to split and combine feeds at the same time (FIFO)



0-10 dB Variable gain

to balance input and output signals



850 - 2450 MHz
operating frequency range



Suitable for HTS applications due to extended bandwidth



Upgraded local control & monitoring via front panel capacitive touchscreen



Compact up to 32 inputs x 32 outputs in a 6U high chassis



Expansion in single increments or with additional matrix modules for larger systems




Self diagnostics with continuous monitoring of amplifiers, CPU's & PSU's



Minimal impact from failure with hot-swap single input & output RF cards, dual power supplies & dual CPU's, fans



Resilience from dual redundant power supplies & CPU modules



Remote control & monitoring via RJ45 Ethernet port with SNMP & web browser interface



Dry contact alarm port & serial communications for amplifier & power supply status





Technical specifications and operating parameters

RF Parameters					
Capacity	32 inputs x 32 outputs, fully populated				
Routing	Fan-in Fan-out (FIFO)		Split and combine feeds at the same time		
Frequency Range	850-2450 MHz (Extended L-band)				
Gain	Maximum	10±1 dB		Typical, mean across band	
	Minimum	0±1 dB		Typical, mean across band	
Gain Control	0 to + 10 in 0.25 dB steps			+5 dB independently settable at each input and output	
RF Connectors	50Ω SMA	50Ω BNC	75Ω BNC	75Ω F-type	
	All ports DC blocked				
Gain Flatness	Full band	±1.25 dB	±1.25 dB	±1.5 dB	±1.5 dB
	Any 36MHz	±0.5 dB	±0.5 dB	±0.5 dB	±0.5 dB
Input Return Loss	Typical	18 dB	18 dB	16 dB	16 dB
	Minimum	14 dB	14 dB	10 dB	10 dB
Output Return Loss	Typical	18 dB	18 dB	16 dB	16 dB
	Minimum	14 dB	14 dB	10 dB	10 dB
Isolation (min between any 2 ports)	I/P - O/P	60 dB			
	I/P - I/P	75 dB			
	O/P - O/P	75 dB			
Group Delay	≤ 1 ns across operational bandwidth				
Noise Figure	0dB Gain	Typical: 18 dB Maximum: 20 dB		Typical, 1 input routed to 1 output	
	10dB Gain	Typical: 12 dB Maximum: 14 dB			
1dB GCP	0dB Gain	-3 dBm		Output power	
	10dB Gain	+3 dBm			
OIP3	0dB Gain	Typical: 10 dBm			
	10dB Gain	Typical: 15 dBm			
OIP2	Typical: 23 dBm , at 0 dB gain				
Switching Time	< 50ms		From receipt of a command to implementation of path change		
Input RF Power	+ 20 dBm		Absolute maximum		

System Control	
Local Control	Via Front Panel capacitive touchscreen
Remote Control	Serial (RS232 or RS422/485) and Ethernet port via RJ45 10BaseT/100 BaseTx. TCP/IP, SNMP & Web browser interface.
Alarms	Dry contact (D-type) & Ethernet (RJ45) for PSU & Amp. status

Power		
PSU Power	85-264Vac 50-60Hz	Fused 2A
AC Consumption	150W	Max. consumption at steady state
PSU	Dual redundant & alarmed	Diode OR. Hot swappable
Hot-swap PSU	Yes	
CPU Redundancy	Dual redundant	Hot swappable
Input Cards	Hot swap	Failure effects only one input port
Output Cards	Hot swap	Failure effects only one output port
MTTR	20 mins. 15 mins to retrieve spare part, 5 mins to replace.	Applies to LRUs only and assumed in house stock
MTBF	Chassis	271,444
	Combiner card	317,227
	Divider card	317,227
		Chassis excludes HMI & RF cards

Environmental	
Operating temperature	0 to 45°C
Storage temperature	-20°C to +75°C
Location	Indoor use only
Humidity	20 to 90% non-condensing
Altitude (operational)	2,000 feet AMSL (Above Mean Sea Level)
Altitude (storage)	3,000 feet AMSL (Above Mean Sea Level)

Physical	
Dimensions	6U high x 560mm deep x 19" wide
Weight	35 kg, fully populated
Colour	RAL9003—White (Semi-Matte)

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.
Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.

