



StingRay RF over Fibre

200 series Optical Fibre to L-band manual gain modules

The SRY-TX-L1-273 and SRY-RX-L1-274 is a manual gain optical transmitter and receiver for RF over Fibre, built in a compact EMC sealed housing which converts L-band (850 to 2450MHz) to 1310nm for transmission over a single mode fibre. It uses a 2-stage optically isolated DFB laser and is suited for transmission up to 10km.

Other options in the StingRay series: The StingRay range is also available with additional features such as RF monitoring ports, high linearity, switchable LNB powering & redundancy systems.

Typical applications:

- General satcoms– teleports, video head-ends, TVRO
- Compact solution for small quantity links such as tactical HQ
- A resilient solution for satellite teleports with transition distances up to 10km

Fibre Modules



Manual gain control
Up to 65dB total



-20dB Monitor port to measure input signal levels



TX & RX module options to transmit and receive signals up to 10 km



Flexibility modules can be housed in outdoor & indoor chassis

Chassis Options



Compact indoor & outdoor chassis options, which can be part populated



Resilience from dual redundant hot-swap power supplies, hot-swap fibre modules & fans



Remote control & monitoring via RJ45 Ethernet port with SNMP & web browser interface



Local control & monitoring via front panel push buttons & display



Indoor chassis showing hot-swap power supply modules, fibre modules and fans



Outdoor Unit (ODU)

Please see separate datasheet for 200 series chassis options.





RF Parameters (TX and RX)		
Model Number	SRY-TX-Y-273-xxxx	SRY-RX-Y-274-xxxx
Frequency Range	850-2450 MHz	
Flatness	950-1950 MHz	±1.0dB (Test Condition: Full TX & RX link, 1m fibre, Input -10dBm, Output -10dBm)
	Any 500 MHz 950-1950 MHz	±0.6dB (Test Condition: Full TX & RX link, 1m fibre, Input -10dBm, Output -10dBm)
	850-2450 MHz	±1.5dB (Test Condition: Full TX & RX link, 1m fibre, Input -10dBm, Output -10dBm)
	Any 36 MHz 950-1950 MHz	±0.25dB (Test Condition: Full TX & RX link, 1m fibre, Input -10dBm, Output -10dBm)
	Any 36 MHz 850-2450 MHz	±0.4dB (Test Condition: Full TX & RX link, 1m fibre, Input -10dBm, Output -10dBm)
Flatness 1+1 link	950-1950 MHz	±1.0dB (Test Condition: With splitter SRY-DIV-L1-289-S5S5 I/P 0dBm, Switch SRY-SW-L1-271-S5S5 O/P 0dBm, 1m fibre link)
	Any 500 MHz 950-1950 MHz	±0.6dB (Test Condition: With splitter SRY-DIV-L1-289-S5S5 I/P 0dBm, Switch SRY-SW-L1-271-S5S5 O/P 0dBm, 1m fibre link)
	Any 36 MHz 950-1950 MHz	±0.25dB (Test Condition: With splitter SRY-DIV-L1-289-S5S5 I/P 0dBm, Switch SRY-SW-L1-271-S5S5 O/P 0dBm, 1m fibre link)
Return Loss	50 ohm SMA	18dB typical, 12dB minimum
	50 ohm BNC	18dB typical, 12dB minimum
Monitor port	-20 dB ±3dB	
Input P1dB (See note 1)	+6dBm Typical, 0dBm Minimum (Test Condition: 1dB compression point. Measured with 1m fibre, 0dB link gain, 1950 MHz)	
Output IP3 (See note 1)	20dBm Typical, 17dBm Minimum (Test Condition: Measured with 1m fibre, 10dB gain, -22 dBm tones at 2150 & 2152 MHz)	
IMD3 (See note 1)	-84dBc, -78dBc Worst Case (Test Condition: Measured with 1m fibre, 10dB gain link, -22 dBm tones at 2150 & 2152 MHz)	
CNR (in any 36 MHz)	-60dB typical, -56dB Worst Case (Test Condition: Measured with 1m fibre, 0dBm RF i/p power, 0 dBm RF o/p total power)	
Noise Figure (See note 1)	24dB Typical, 27dB Worst Case (Test Condition: Measured with 1m fibre, 0dBm RF i/p power, 0 dBm o/p power N.B. 0dB gain)	
Optical Wavelength	1310 ± 10 nm	1100 to 1650 nm (Optimised for 1310 nm and 1550 nm)
Max RF Input	+0dBm total power (Damage level)	
SFDR	112 dB/Hz ^{2/3} typ., 108 dB/Hz ^{2/3} min (Test condition: 1m fibre, 10dB gain, -22dBm tones at 2150 & 2152 MHz)	
Phase Noise	10 Hz	<-70dBc/Hz (Test condition: SRY-LX-L1-273, 1m fibre, 0dBm RF i/p power, 0dBm o/p power)
	100 Hz	<-90dBc/Hz (Test condition: SRY-LX-L1-273, 1m fibre, 0dBm RF i/p power, 0dBm o/p power)
	1 kHz	<-100dBc/Hz (Test condition: SRY-LX-L1-273, 1m fibre, 0dBm RF i/p power, 0dBm o/p power)
	10 kHz	<-110dBc/Hz (Test condition: SRY-LX-L1-273, 1m fibre, 0dBm RF i/p power, 0dBm o/p power)
	100 kHz	<-120dBc/Hz (Test condition: SRY-LX-L1-273, 1m fibre, 0dBm RF i/p power, 0dBm o/p power)
	1 MHz	<-130dBc/Hz (Test condition: SRY-LX-L1-273, 1m fibre, 0dBm RF i/p power, 0dBm o/p power)
Laser Type	DFB (Two stage optical isolator for improved performance)	
Optical Power output	+6 ±2.5dBm	N/A
Optical Power in	N/A	0 to 4.5dBm
Power Consumption	6W	4W
Manual Gain Control (in 0.25 dB steps)	+30dB	35dB
Range of max i/p level for optimised 0 dB link	-30 to 0dBm (with SRY-RX-L1-274)	
RF Output Range	-	
MTBF	>172,000	>232,000
RF Connectors	BNC 50 Ω (B5) or SMA 50 Ω (S5)	
Optical Connectors	FC/APC (FA) or SC/APC (SA)	
Operating Temperature	-20 to +60 °C	
Storage Temperature	-40 to +90 °C	
Location	Indoor use	
Humidity	20 to 90% non-condensing. Relative Humidity	
Altitude	10,000 feet AMSL (Above Mean Sea Level) - Operational 30,000 ft AMSL (Above Mean Sea Level) - Storage/Transport	
Dimensions	87.8 x 18 x 150 mm	
Weight	0.35 kg	

Note 1: All RF measurements are given with T273 RF input to the laser 'RF Out Pwr' set to 0dBm. Higher level here will give better P1dB at the expense of Noise.