



2-way Dual L-Band Active Splitter

with switchable LNB powering,
10MHz injection, current monitoring
& local & remote control

Typical applications:

- Satellite operators, VSAT, teleports, and broadcasters
- High resilience RF distribution where optimum satellite signal quality is required

Compact
housed in a 1U
high chassis

850 to 2150 MHz
operating frequency range.

LNB Powering
13/18V & 22 KHz tone

Local control & monitoring via front panel push buttons to select LNB voltage & tone & output switch



Resilience
from dual redundant hot-swap power supplies

Dry contact alarm port
for PSU failure

10MHz Injection onto L-band inputs

Remote control & monitoring via RJ45 Ethernet port with SNMP, web browser interface & RS232/485 Serial port



2-way Dual L-band Active Splitter with switchable LNB powering, 10MHz injection, current monitoring & local & remote control

Technical specifications and operating parameters

RF Parameters						
Capacity	Dual 2-Way Splitter					
Frequency Range	850 to 2150MHz (L-band)					
RF Connectors	50Ω SMA	50Ω N-Type	50Ω BNC	75Ω BNC	75Ω F-Type	
Insertion Loss	L-Band	1±0.75 dB	1±0.75 dB	1±1.0 dB	1±1.25 dB	1±1.25 dB
	10MHz into L-band ports	<4.5 dB	<4.5 dB	<4.5 dB	<4.5 dB	<4.5 dB
Gain Flatness	Full band	±1.0 dB	±1.2 dB	±1.5 dB	±1.8 dB	±2.0 dB
	Any 36 MHz	±0.25 dB	±0.25 dB	±0.5 dB	±0.75 dB	±1.0 dB
Input Return Loss	Typical	14 dB	14 dB	12 dB	12 dB	12 dB
	Minimum	10 dB	10 dB	10 dB	8 dB	8 dB
Output Return Loss	Typical	18 dB	18 dB	14 dB	12 dB	12 dB
	Minimum	12 dB	12 dB	12 dB	8 dB	8 dB
1dB GCP	+5 dBm					
Noise Figure	10.5 dB					
Input Isolation	>50 dB					
Output Isolation	Selected	>18 dB				
	Not Selected	>80 dB				
Input RF Power	+16 dBm			Absolute maximum		

Preliminary Specifications

Power		
PSU Power	85-264Vac 50-60Hz	Fused 2A
AC Consumption	38W	Max. consumption at steady state
LNB Power	13/18V nominal, 0.5A via common (RF IN) ports	Each channel fused and monitored
PSU	Dual redundant and alarmed	Diode OR. Hot Swap
Hot-Swap PSU	Yes	
MTBF (hours)	334,199	

System Control		
Remote Control and monitoring	Via RS232/485 serial port and RJ45 Ethernet port on rear panel	Enables selection of LNB voltage and provides monitoring of LNB current and alarms status
Local Control	Via front panel push buttons	Enables selection of LNB voltage & output switch position
Display	Front panel LEDs for voltage selection & power supply status	
Alarms	Dry contact (D-type) & Ethernet (RJ45)	PSU Failure and low/high LNB Current

Environmental	
Operating temperature	0 to 45°C
Location	Indoor use only
Storage temperature	-20°C to +75°C
Humidity	20 to 90% non-condensing
	Relative Humidity
Altitude	10,000 feet AMSL
	Above mean sea level

Physical	
Dimensions	1U high x 350mm deep x 19" wide
Weight	4 kg
Colour	White 00-E-55 semi-gloss

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.
Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.



Esatcom Inc.
www.esatcom.com
Tel: 718.276.0800
Email: sales@esatcom.com

