



Model Number: D0108S1ULA-22245-B5B5

8-way Single L-band Active LD Series Splitter

with switchable LNB Powering



The compact 8-way active splitter is part of the LD Splitter Series and is designed to provide affordable L-band splitting in a 1U high, 19" rack mountable chassis.

Front View of Model D0108S1ULA-22245-B5B5

Covering the full range of L-band, 850-2150MHz, this shelf also offers dual redundant power supplies, and is also able to offer switchable LNB powering.

Front panel LED's indicate the condition of the dual redundant power supplies and the status of the LNB bias.



Rear View of Model D0108S1ULA-22245 with 75 ohm BNC connectors

This particular unit is supplied with 50 ohm BNC RF connectors, but is available in a range of impedances and RF connectors (not N-type RF connectors).



Model Number: D0108S1ULA-22245-B5B5

8-way Single L-band Active LD Series Splitter with switchable LNB Powering

RF Engineering and Custom Build

Technical specifications and operating parameters

RF Parameters

Capacity	8- way
Frequency Range	850-2150 MHz (L-band)
Gain	0 dB \pm 1.5 dB nominal, mean across band
Flatness	850-2150MHz \pm 1.0 dB typical
1dB Compression	-5 dBm
IP3	5 dBm
Noise Figure	10 dB
Isolation	25 dB (between any 2 output ports)
Input Return Loss	15 dB typical
Output Return Loss	15 dB typical

Power

AC Power	85-264V AC (50/60Hz), Fused 2A
LNB Power	18V DC, 310 mA via common port, switchable on/off
PSU	Dual redundant
Hot-swap PSU	No

System Control

Display	Front Panel LED's for Power & PSU status
Local Control	LNB Powering switch on rear panel

Environmental

Operating temperature	0 to 45°C
Location	Indoor use only
Storage temperature	-20°C to +75°C
Humidity	85% non-condensing

Physical

Input Connectors	BNC
Input Impedance	50 Ω
Output Connector	BNC
Output Impedance	50 Ω
Dimensions	1U high x 220mm deep x 19" wide
Weight	2 kg
Colour	White 00-E-55 semi-gloss

Key Features

Housed in a compact 1U high rack
Dual redundant power supplies
Switchable LNB Powering
Front Panel LED's for LNB & PSU status



Esatcom Inc.
www.esatcom.com
 Tel: 718.276.0800
 Email: sales@esatcom.com

