



LS12 2150P LS122150P1FNA000 12-Way Passive Splitter (950-2150 MHz)

QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO 9001:2008

General Description:

The **LS122150P1FNA000** is a commercial quality passive 12-way splitter that meets strict level, match, and loss specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and enables the splitting of RF signals with repeatable performance over the entire frequency range and across all I/O ports. Output port 1 is power passing for LNB power from a satellite receiver. Since DC paths are diode protected, LNB power is redundant if both paths are powered.

Note: All unused RF output ports must have 75 Ω terminations. A rear panel terminal is provided for external LNB power insertion.

Specifications:

Frequency:	950-2150 MHz
Impedance:	75 Ω
Insertion Loss:	17 \pm 2 dB
Frequency Response:	\pm 2 dB
Isolation:	20 dB
Input Return Loss:	14 dB
Output Return Loss:	14 dB
RF Connectors:	Type F, 75 Ω
Mechanical:	1 RU (1.75" H x 19" W x 6.5" D)
Weight:	3.5 lbs. gross (boxed), 2.5 lbs. net
Certifications:	CE



Esatcom Inc.
www.esatcom.com

Tel:
718.276.0800

Email:
sales@esatcom.com