



LC12 2150A LC122150A1FXA000 12-Way Active Combiner (950-2150 MHz)

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

General Description:

The **LC122150A1FXA000** is a commercial quality 12-way combiner that meets strict level and match specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and enables the combining of RF signals with repeatable performance over the entire frequency range and across all I/O ports.

Note: All unused RF input ports must have 75 Ω terminations.

Specifications:

Frequency:	950-2150 MHz
Impedance:	75 Ω
P1dB:	-2 dBm @ each input
Insertion Loss:	0 \pm 2 dB
Frequency Response:	\pm 2 dB
Isolation:	18 dB
Input Return Loss:	12 dB
Output Return Loss:	12 dB
Noise Figure:	19 dB
RF Connectors:	Type F, 75 Ω
Power Requirements:	100-240 V~, 50/60 Hz
Power Consumption:	5 W
Operating Temperature:	0 to +50 $^{\circ}$ C at up to 95% RH, non-condensing
Storage Temperature:	-10 to +70 $^{\circ}$ C at up to 95% RH, non-condensing
Mechanical:	1 RU (1.75" H x 19" W x 6.5" D)
Weight:	5 lbs. gross (boxed), 3 lbs. net



Esatcom Inc.
www.esatcom.com

Tel:
718.276.0800

Email:
sales@esatcom.com